



SeaFET Summary Report



Serial Number: 245

Firmware Rev: 3.8.0

Operator: Cindy

Comment:

Ancillary	Value	Setting	Value
Total Disk Space (byte)	3954802688	Serial Baud Rate	115200
Free Disk Space (byte)	3954409472	Operation Mode	Periodic
Main Voltage (V)	0.000	Transmitted Frame Format	FULL_ASCII
Main Battery Voltage (V)	12.9	Logging Frame Format	FULL_ASCII
Isolated Battery Voltage (V)	6.5	Periodic Interval	20 min
Clock Time	2019/07/23.23:08:15	Periodic Offset (s)	0
Supports External Pump	true	Samples in Average	30
Supports Integrated CTD	true	Frames in Burst	10
		Sampling Window Enabled	true
		Sampling Window Start	2019-08-13
		Sampling Window End	2020-08-13
		Data Log File Type	Daily
		Data Log File Max Size (KB)	1024
		Message Logging Level	DEBUG
		Message Log File Max Size (KB)	2048
		Transmit Diagnostic Messages	true
		External Pump Enabled	false
		External Pump Pumping Time (s)	5
		External Pump Flushing Time (s)	5
		SBE37-SMP-ODO CTD Enabled	false
		SBE37-SMP-ODO Power CTD	true
		SBE37-SMP-ODO Output CTD Frames	false
		SBE37-SMP-ODO Sampling Timeout (s)	120
		ISFET Sample Delay (s)	0
		On-Board Salinity (PSU)	32.5

Serial Number: 245
Operator: Cindy
Comment:

Firmware Rev: 3.8.0

Ancillary	Value	Setting	Value
		Internal Reference Coefficients (V,V/K)	-1.239128,-0.001101
		External Reference Coefficients (V,V/K)	-1.244415,-0.001048
		Thermistor Coefficients	340.982,-9.10257E-5,-95.08807,0.9653703